

## Brand New Chiller Carrier AQUA Force 30XW-V1280A009 –VAR18 Year of build 03-2019 Zero running hours

## Minor transport damage



## **Description :**

The Carrier AQUA Force 30XW-V1280A009 –VAR18 has minor transport damage to the electrical cabinets. No mayor items are damaged . Latest model Chiller driven by two VSD Thunderbolts Screw compressor blocks.

We offer this unit for sale as it is or complete restored .



RM Support BV Burenweg 14, 7621 GX Borne ( ind area De Veldkamp Noord) , The Netherlands Phone: +31 (0)74 256 9777, Cell phone: +31 (0)6 427 20 672 E-mail: <u>info@rm-support.nl</u>, Internet: <u>www.rm-support.nl</u>, <u>www.rm-support.com</u> Commercial Reg. Enschede No. 08133380, VAT No. NL 82 28 96 965 B01, IBAN: NL45 RABO 0317 2838 20

Unless notified or agreed on in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the Chamber of Commerce on November 14, 2013, number: 08133380. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: www.rm-support.nl.

Page 1



## **Capacity indication** :

**Condition by Heating full load** -1428 KW COP 4,61 (Evaporator entry / exit water temperature  $10^{\circ}C/7^{\circ}C$ - condenser entry / exit water temperature  $40^{\circ}C/45^{\circ}C$ , fouling factor evaporator / condenser  $0M^{2}K/W$ )

**Condition by cooling full load** -1305 KW COP 5,50 (Evaporator entry / exit water temperature  $12^{\circ}C/7^{\circ}C$ - condenser entry / exit water temperature  $30^{\circ}C/35^{\circ}C$ , fouling factor evaporator / condenser  $0M^{2}K/W$ )



The new Thunderbolt twin rotor Compressors are special designed for VSD Drive, the oversized bearing construction, advanced Lubrication system together with additional oil separator in the condenser, the sound reducer in the discharge line realize compact effective trouble free working long life of operation against a very low energy consumption.



Page 2



RM Support BV Burenweg 14, 7621 GX Borne ( ind area De Veldkamp Noord) , The Netherlands Phone: +31 (0)74 256 9777, Cell phone: +31 (0)6 427 20 672 E-mail: info@rm-support.nl, Internet: www.rm-support.nl, www.rm-support.com Commercial Reg. Enschede No. 08133380, VAT No. NL 82 28 96 965 B01, IBAN: NL45 RABO 0317 2838 20

Unless notified or agreed on in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the Chamber of Commerce on November 14, 2013, number: 08133380. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: www.rm-support.nl.



Liquid : R134a 240 kg Weight in operation : 7398 kg Length: 4730 mm Width: 1255 mm Height: 1997 mm

A CONTRACTOR OF THE OWNER OWNER OF THE OWNER OWNE OWNER OWNE	CARRENTS	San Star		1952		234	
1- SERIAL NUMBER NUMERO DI SERIE	M20190	02595	;				
2- MODEL	30XW-V			00_		-	· · · · ·
MODELLO 47- DESCRIPTION	· · · · · ·	1200/1	50	09-		C	<b>E</b> 0062
DESCRIZIONE							
3- VARIANT VERSIONE	VAR18						
4- YEAR OF MANUFACTU ANNO E DATA DI CO	JRE AND TEST D STRUZIONE	ATE 19/03/	201	.9			
48- HERMETICALLY SEA APPARECCHIATURE				N			
49- CONTAINS FLUORIN CONTIENE GAS FLUO	ARED GREENHOU DRURATI EFFET	SE GASES TO SERRA		Y			
25- FLUID DURING TRA LIQUIDI DURANTE I		R-134a		240	.00	kg	
5- REFRIGERANT REFRIGERANTE	R-134a	6- F G	PED	GROUP 2 PO PED 2		GWP	1430
50- CIRCUIT CIRCUITO		A	1	В	/	C	
7- FACTORY CHARGE CARICO FABBRICA		120.00	1 :	120.00	1	*	kg
51- CHARGE ADDED ON CARICO AGGIUNTO			1		/		kg
52- TOTAL CHARGE CARICO TOTALE		120.00	1 :	120.00	/	*	kg
		171.60	1 1	171.60	/	*	t.eq.CO2
9- INERTING MEDIUM CARICA DI TENUT							L DDE CEUDE
		21	ALT	GH PRESS	IONE	BAS	W PRESSURE SA PRESSIONE
10- ALLOWABLE PRESS MIN/MAX PRESSIO	SURE MIN/MAX	(PS) (-1.1 -99		/ 21.0 / 2100.0	bar kPa		21.0 bar) 2100.0 kPa
11- ALLOWABLE TEMPI	ERATURE MIN/MA	(TS) -20			°C	-20.0 /	72.0. °C
MTN/MAY TEMPER	ATTIRA AMISSIBIL	E and the second second		/ *	bar	* - /	* bar
12- PRESSURE SAFET TARATURA PRESSI 13- RELIEF VALVE SI PRESSIONE DI II	ETTING	LA DI SICURF	77A	*	bar		* bar
	SETTING NTERVENTO DEI D			*	bar		* bar
14- UNIT LEAK TEST PRESSIONE DI P	PRESSURE				15.	.0 bar	
15- VOLTAGE 4 TENSIONE	400 V +10	% -10 % 1		HASES 3 ASI		FREQUENZA	(~ 50 Hz
18- MAXIMUM AMPS MAX CORRENTE		300.00 A			44-	IP 23 IP	
19- MAX POWER INPU POTENZA ASSORE 20- NET WEIGHT	BITA	193.00 kW		6 %			
PESO NETTO		NB .					
Carrier MANUFACTURED IN FRANCE BY CARRIER SCS - 01120 MONTLUEL - FRANCE							
AN AFFLITATED COMPANY OF CARRIER CORPORATION FARMINGTON CT, USA							
	1999 - 1999 -		"		PLS	_TriCkt_V	4r1
C. Statesta			10				

Page 3



RM Support BV Burenweg 14, 7621 GX Borne ( ind area De Veldkamp Noord) , The Netherlands Phone: +31 (0)74 256 9777, Cell phone: +31 (0)6 427 20 672 E-mail: <u>info@rm-support.nl</u>, Internet: <u>www.rm-support.nl</u>, <u>www.rm-support.com</u> Commercial Reg. Enschede No. 08133380, VAT No. NL 82 28 96 965 B01, IBAN: NL45 RABO 0317 2838 20

Unless notified or agreed on in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the Chamber of Commerce on November 14, 2013, number: 08133380. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: www.rm-support.nl.