

**Technical details Eliminex®**


The Eliminex eliminate water and dirt from 3 micron from the main air supply line.

The pressure drop is only 0,06 bar.

The connection are from 3/4 inch till 2 inch BSPP (British Standard parallel pipe) and flange connections from 3 inch till 6 inch.

The housing is in two variants: Aluminium and epoxy coated steel.

The max. volume flow is 8827 Nm<sup>3</sup>/hr

A Automatic drain valve is standard installed.

**Eliminex Aluminium housing**

Model number	Optimal Volume flow Nm <sup>3</sup> /hr	Max. volume flow Nm <sup>3</sup> /hr	Max. operation pressure bar	Max. operation temperature °C
IP-120-MP6-F	96	193	14	80
IP-175-MP8-F	140	280	14	80
IM-300-P12-F	240	481	14	80
IM-300-P16-F	240	481	14	80
IM-400-P12-F	321	642	14	80
IM-700-P16-F	562	1124	14	80

**Eliminex Aluminium housing**

Model number	Connection Inch BSPP	Weight Kg	H mm	W mm	D mm
IP-120-MP6-F	¾	3,2	394	127	127
IP-175-MP8-F	1	3,2	394	127	127
IM-300-P12-F	1 1/2	13,2	686	198	198
IM-300-P16-F	2	13,2	686	198	198
IM-400-P12-F	1 1/2	16,8	762	216	216
IM-700-P16-F	2	16,8	762	216	216

**IM-Supply B.V.**

Mekkelhotsweg 20 7523 DE Enschede , The Netherlands

Phone: +31 (0)74 256 9777, E-mail: [info@rm-support.nl](mailto:info@rm-support.nl)

----- Commercial Reg.-Enschede-No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----  
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website:

Eliminex steel housing				
Model number	Optimal Volume flow Nm3/hr	Max. volume flow Nm3/hr	Max. operation pressure bar	Max. operation temperature °C
IM-2500-MFDX	2006	4012	10,5	50
IM-2500-MFEX	2006	4012	10,5	50
IM-2500-MFFX	8827	8827	10,5	50

Eliminex steel housing					
Model number	Connection Flange inch	Weight Kg	H mm	W mm	D mm
IM-2500-MFDX	3	113,4	1219	464	407
IM-2500-MFEX	4	120,2	1219	518	407
IM-2500-MFFX	6	163,3	1524	594	407

**IM-Supply B.V.**

Mekkelhotsweg 20 7523 DE Enschede , The Netherlands

Phone: +31 (0)74 256 9777, E-mail: [info@rm-support.nl](mailto:info@rm-support.nl)

----- Commercial Reg.-Enschede-No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----  
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: