

Technical details Eliminex® Combo



The Eliminex combo is combination of Eliminex and coalescing filter, a two-stage system.

Eliminate water, oil and dirt bigger than 0.01 micron from the main air supply line.

The pressure drop is only 0,14 bar.

Connections: from 3/4 inch till 2 inch BSPP (British Standard parallel pipe).

The housing is Aluminium.

The max. volume flow is 1124 Nm³/hr

Standard is an automatic drain valve installed.

Eliminex Combo met Aluminium behuizing

Model nummer	Optimale Volume stroom Nm ³ /hr	Maximale volumestroom Nm ³ /hr	Max bedrijfsdruk bar	Max. Bedrijfstemperatuur °C
IP-090-MP6-DC	72	114	14	80
IP-150-MP8-DC	120	240	14	80
IM-300-P12-DC	240	481	14	80
IM-300-P16-DC	240	481	14	80
IM-400-P12-DC	321	642	14	80
IM-700-P16-DC	562	1124	14	80

Eliminex Combo met Aluminium behuizing

Model nummer	Aansluiting Inch BSPP	Gewicht Kg	hoogte mm	Breedte mm	Diepte mm
IP-090-MP6-DC	¾	6,8	482	154	117
IP-150-MP8-DC	1	6,8	482	254	117
IM-300-P12-DC	1 1/2	26,2	686	419	198
IM-300-P16-DC	2	26,2	686	419	198
IM-400-P12-DC	1 1/2	32,7	863	482	216
IM-700-P16-DC	2	33,6	863	482	216

IM-Supply B.V.

Mekkeholtsweg 20, 7523DE Enschede, The Netherlands

Phone: +31 (0)74 256 9777, E-mail: info@rm-support.nl

----- Commercial Reg.-Enschede-No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: