

Technische gegevens Eliminex®



De Eliminex verwijdert water en verontreinigen vanaf 3 micron uit de hoofdleiding met een zeer laag drukverschil van 0,06 bar.

Er zijn verschillende aansluitingen van 3/4 inch tot 2 inch BSP (British Standard parallel pipe) en als flens uitvoering vanaf 3 inch tot 6 inch.

De behuizing is er in de uitvoeringen Aluminium en epoxy gecoat staal.

De maximale volumestroom is 8827 Nm³/hr

Een automatische drain valve is standaard gemonteerd.

Eliminex met Aluminium behuizing

Model nummer	Optimale Volume stroom Nm ³ /hr	Maximale volumestroom Nm ³ /hr	Max bedrijfsdruk bar	Max. Bedrijfstemperatuur °C
IP-120-MP6-F	96	193	14	80
IP-175-MP8-F	140	280	14	80
IM-300-P12-F	240	481	14	80
IM-300-P16-F	240	481	14	80
IM-400-P12-F	321	642	14	80
IM-700-P16-F	562	1124	14	80

Eliminex met Aluminium behuizing

Model nummer	Aansluiting Inch BSP	Gewicht Kg	hoogte mm	Breedte mm	Diepte mm
IP-120-MP6-F	¾	3,2	394	127	127
IP-175-MP8-F	1	3,2	394	127	127
IM-300-P12-F	1 1/2	13,2	686	198	198
IM-300-P16-F	2	13,2	686	198	198
IM-400-P12-F	1 1/2	16,8	762	216	216
IM-700-P16-F	2	16,8	762	216	216

IM-Supply B.V.

Mekkelhotsweg 20 7523 DE Enschede , The Netherlands

Phone: +31 (0)74 256 9777, E-mail: info@rm-support.nl

----- Commercial Reg.-Enschede.No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website:

Eliminex met stalen behuizing				
Model nummer	Optimale Volume stroom Nm3/hr	Maximale volumestroom Nm3/hr	Max bedrijfsdruk bar	Max. Bedrijfstemperatuur °C
IM-2500-MFDX	2006	4012	10,5	50
IM-2500-MFEX	2006	4012	10,5	50
IM-2500-MFFX	8827	8827	10,5	50

Eliminex met stalen behuizing					
Model nummer	Aansluiting Flens inch	Gewicht Kg	hoogte mm	Breedte mm	Diepte mm
IM-2500-MFDX	3	113,4	1219	464	407
IM-2500-MFEX	4	120,2	1219	518	407
IM-2500-MFFX	6	163,3	1524	594	407

IM-Supply B.V.

Mekkelhotsweg 20 7523 DE Enschede , The Netherlands

Phone: +31 (0)74 256 9777, E-mail: info@rm-support.nl

----- Commercial Reg.-Enschede.No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: