

Technical details Eliminizer ©



The eliminizer produces clean, dry air at the supply point. The recommended installation is max 5 meters of the air supply point.

The Eliminizer is available with different connections from ¼ inch till 1 inch BSPP (British Standard parallel pipe).

There are 3 housings available : polycarbonate, epoxy coated steel and RVS .

The Eliminizer is suitable to volume flows of 240 Nm³/hr

The max pressure drop is 0.35 bar.

Eliminate condensing liquids and debris above 1 micron.

A automatic drain valve is standard.

Eliminizer with polycarbonate housing

Model number	Optimal Volume flow Nm ³ /hr	Max volume flow Nm ³ /hr	Max operaton pressure bar	Max. operation temperature °C
3P-020-PP2-F	16	32	10,5	50
3P-035-PP2-F	27	56	10,5	50
3P-035-PP3-F	27	56	10,5	50
3P-035-PP4-F	27	56	10,5	50
3P-060-PP4-F	48	96	10,5	50
3P-090-PP6-F	72	115	10,5	50
3P-150-PP8-F	120	240	10,5	50

Dimension polycarbonate housing

Model number	connection Inch BSPP	weight Kg	h mm	w mm	D mm
3P-020-PP2-F	1/4	0.9	190	76	66
3P-035-PP2-F	1/4	2,3	292	95	95
3P-035-PP3-F	3/8	2,3	292	95	95
3P-035-PP4-F	1/2	2,3	292	95	95
3P-060-PP4-F	1/2	2,3	292	95	95
3P-090-PP6-F	3/4	3,2	393	127	127
3P-150-PP8-F	1	3,2	393	127	127

IM-Supply B.V.

Mekkelholtsweg 20 7523 DE Enschede, The Netherlands

Phone: +31 (0)74 2569777, E-mail: info@rm-support.nl

----- Commercial Reg.- Enschede-No. 55672264, VAT No.-NL-851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website:

Eliminizer met steel housing				
Model number	Optimal Volume flow Nm3/hr	Max volume flow Nm3/hr	Max operaton pressure bar	Max. operation temperature °C
3P-020-MP2-F	16	32	14	80
3P-035-MP4-F	27	56	10,5	80
3P-060-MP4-F	48	96	10,5	80
3P-090-MP6-F	72	144	10,5	80
3P-090-MP8-F	120	240	14	80

Eliminizer Steel housing					
Model number	connection Inch BSPP	weight Kg	h mm	w mm	D mm
3P-020-MP2-F	1/4	0,9	190	76	66
3P-035-MP4-F	1/2	1,8	292	95	95
3P-060-MP4-F	1/2	1,8	292	95	95
3P-090-MP6-F	3/4	3,2	393	127	127
3P-090-MP8-F	1	3,2	393	127	127

Eliminizer met RVS 316 behuizijng				
Model number	Optimal Volume flow Nm3/hr	Max volume flow Nm3/hr	Max operaton pressure bar	Max. operation temperature °C
3P-060-SP4-F	48	96	10,5	50

Eliminizer met RVS316 behuizing					
Model number	connection Inch BSPP	weight Kg	h mm	w mm	D mm
3P-060-SP4-F	1/2	1,7	283	83	83

IM-Supply B.V.

Mekkelholtsweg 20 7523 DE Enschede, The Netherlands

Phone: +31 (0)74 2569777, E-mail: info@rm-support.nl

----- Commercial Reg.- Enschede-No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: