

Technische gegevens Eliminer Combo



De eliminer combo produceert Schone , droge en olie vrije lucht bij het afname punt. De eerste fase wordt verzorgd door de eliminer, welke de perslucht zuivert van water en verontreinigen en de tweede fase wordt verzorgd door een effectieve coalescer element, welke de olie afvangt tot 0,01 micron

De aanbevolen montage is bij het afname punt of max 5 meter van het afname punt.

De Eliminer is verkrijgbaar met verschillende aansluitingen van ¼ inch tot 1 inch BSPP (British Standard parallel pipe).

Daarnaast in 3 verschillende behuizing : polycarbonaat, epoxy gecoate stalen rvs behuizing.

Eliminer combo met polycarbonaat behuizing

Model nummer	Optimale Volume stroom Nm3/hr	Maximale volumestroom Nm3/hr	Max bedrijfsdruk bar	Max. Bedrijfstemperatuur °C
3P-020-PP2-DC	16	21	10,5	50
3P-060-PP2-DC	48	96	10,5	50
3P-060-PP3-DC	48	96	10,5	50
3P-060-PP4-DC	48	96	10,5	50
3P-090-PP6-DC	72	120	10,5	50
3P-150-PP8-DC	120	240	10,5	50

Eliminer combo met polycarbonaat behuizing

Model nummer	Aansluiting Inch BSPP	Gewicht Kg	hoogte mm	Breedte mm	Diepte mm
3P-020-PP2-DC	¼	2,7	190	170	66
3P-060-PP2-DC	¼	3,6	292	210	95
3P-060-PP3-DC	3/8	3,6	292	210	95
3P-060-PP4-DC	½	3,6	292	210	95
3P-090-PP6-DC	¾	6,3	393	275	127
3P-150-PP8-DC	1	6,3	393	275	127

IM-Supply B.V.

Mekkeholtsweg 20, 7523 DE Enschede , The Netherlands

Phone: +31 (0)74 256 9777, E-mail: info@rm-support.nl

----- Commercial Reg.-Enschede-No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website:

Eliminizer combo met stalen behuizing

Model nummer	Optimale Volume stroom Nm ³ /hr	Maximale volumestroom Nm ³ /hr	Max bedrijfsdruk bar	Max. Bedrijfstemperatuur °C
3P-020-MP2-DC	16	32	14	80
3P-060-MP4-DC	48	96	10,5	80
3P-090-MP6-DC	72	144	10,5	80
3P-150-MP8-DC	120	240	14	80

Eliminizer Combo met stalen behuizing

Model nummer	Aansluiting Inch BSPP	Gewicht Kg	hoogte mm	Breedte mm	Diepte mm
3P-020-MP2-DC	1/4	2,2	190	170	66
3P-060-MP4-DC	1/2	4	292	210	95
3P-090-MP6-DC	3/4	6,8	393	275	127
3P-150-MP8-DC	1	6,8	393	275	127

Eliminizer Combo met RVS 316 behuizing

Model nummer	Optimale Volume stroom Nm ³ /hr	Maximale volumestroom Nm ³ /hr	Max bedrijfsdruk bar	Max. Bedrijfstemperatuur °C
3P-060-SP4-DC	48	96	10,5	50

Eliminizer Combo met RVS316 behuizing

Model nummer	Aansluiting Inch BSPP	Gewicht Kg	hoogte mm	Breedte mm	Diepte mm
3P-060-SP4-DC	1/2	3,8	283	178	83

IM-Supply B.V.

Mekkeholtweg 20, 7523 DE Enschede , The Netherlands

 Phone: +31 (0)74 256 9777, E-mail: info@rm-support.nl

----- Commercial Reg.-Enschede-No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: