

## Technical Details Eliminer © Combo



De eliminer combo produces clean, dry and oil free air at the supply point. The first phase is water reduction by the eliminer. The second phase is the oil reduction by an effective coalescing element. Effectivity till 0,01 micron  
The recommended point of installation is max. 5 meters from the air supply point.

The Eliminer is available in connections from ¼ inch till 1 inch BSPP (British Standard parallel pipe).

3 types of housing are available: polycarbonate, epoxy coated steel and RVS.

The Eliminer is suitable till volume flow of 240 Nm<sup>3</sup>/hr  
The max. pressure drop is 0.35 bar.

Eliminer combo polycarbonate housing				
Model number	Optimal Volume flow Nm <sup>3</sup> /hr	Max. volume flow Nm <sup>3</sup> /hr	Max operation pressure bar	Max. operation temperature °C
3P-020-PP2-DC	16	21	10,5	50
3P-060-PP2-DC	48	96	10,5	50
3P-060-PP3-DC	48	96	10,5	50
3P-060-PP4-DC	48	96	10,5	50
3P-090-PP6-DC	72	120	10,5	50
3P-150-PP8-DC	120	240	10,5	50

Eliminer combo steel housing				
Model number	Optimal Volume flow Nm <sup>3</sup> /hr	Max. volume flow Nm <sup>3</sup> /hr	Max operation pressure bar	Max. operation temperature °C
3P-020-MP2-DC	16	32	14	80
3P-060-MP4-DC	48	96	10,5	80
3P-090-MP6-DC	72	144	10,5	80
3P-150-MP8-DC	120	240	14	80

Eliminer RVS 316 housing				
Model number	Optimal Volume flow Nm <sup>3</sup> /hr	Max. volume flow Nm <sup>3</sup> /hr	Max operation pressure bar	Max. operation temperature °C
3P-060-SP4-DC	48	96	10,5	50

### IM-Supply B.V.

Mekkelholtsweg 20, 7523 DE Enschede, The Netherlands

Phone: +31 (0)74 256 9777, E-mail: [info@rm-support.nl](mailto:info@rm-support.nl)

----- Commercial Reg.-Enschede.No. 55672264, VAT No.-NL.851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----  
-Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website:

**Dimensions:**

Eliminizer combo polycarbonate housing					
Model number	Connection Inch BSPP	Weight Kg	h mm	w mm	D mm
3P-020-PP2-DC	¼	2,7	190	170	66
3P-060-PP2-DC	¼	3,6	292	210	95
3P-060-PP3-DC	3/8	3,6	292	210	95
3P-060-PP4-DC	½	3,6	292	210	95
3P-090-PP6-DC	¾	6,3	393	275	127
3P-150-PP8-DC	1	6,3	393	275	127

Eliminizer combo Steel housing					
Model number	Connection Inch BSPP	Weight Kg	h mm	w mm	D mm
3P-020-MP2-DC	1/4	2,2	190	170	66
3P-060-MP4-DC	1/2	4	292	210	95
3P-090-MP6-DC	3/4	6,8	393	275	127
3P-150-MP8-DC	1	6,8	393	275	127

Eliminizer combo RVS316 housing					
Model number	Connection Inch BSPP	Weight Kg	h mm	w mm	D mm
3P-060-SP4-DC	1/2	3,8	283	178	83

**IM-Supply B.V.**

Mekkelholtsweg 20, 7523 DE Enschede , The Netherlands

Phone: +31 (0)74 256 9777, E-mail: [info@rm-support.nl](mailto:info@rm-support.nl)

----- Commercial Reg.-Enschede.No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----  
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: