

## Technical details Stealth



The Stealth is a filter –dryer and works at a identical principle as the de Eliminizer. The Stealth is available with and with pressure regulator.

Produces clean, dry air for critical applications at the air supply point. Recommended is to install the Stealth within max. 5 meters from the air supply point.

The aluminum housing has a connection of 1/2 inch BSPP (British Standard Parallel Pipe).

The Stealth is suitable till volume flows of 96 m3/hour

The max. pressure drop is 0.35 bar. Standard is a manual operated drain valve installed .



**Stealth aluminium behuizing**

Modelnummer	Optimale volumestroom m3/uur	Maximale volumestroom m3/uur	Max. bedrijfsdruk in bar	Max. bedrijfstemp. in °C
STLH-6900 zonder drukregelaar	48	96	14	80
STLH-6950-PB met drukregelaar	48	96	14	80

**Stealth aluminium behuizing**

Modelnummer	Aansluiting inch BSPP	Gewicht kg	Hoogte mm	Breedte mm	Diepte mm
STLH-6900 zonder drukregelaar	1/2	1,8	292	95	95
STLH-6950-PB met drukregelaar	1/2	2,0	327	156	96

### IM-Supply B.V.

Mekkelholtsweg 20, 7523 DE Enschede , The Netherlands

Phone: +31 (0)74 256 9777, Mail: [info@rm-support.nl](mailto:info@rm-support.nl)

----- Commercial Reg.-Enschede-No. 55672264, VAT No.-NL 851812211B01, IBAN: NL64-ING 00 06-38-68-03 -----  
 -Unless notified or agreed in writing, our General conditions govern all our tenders for and agreements on all our deliveries and services, registered by the trading chamber on under number: 55672264. Any other conditions are herewith explicitly rejected by us. A copy of the conditions mentioned above is included or can be send to you on request, free of charge. The conditions are also available on our website: